


SKU SP-LP0511L Job Name: Mark: Submitted By: Date: 06/15/2023

MultiSpec SP-LP0511L 50/80/110 CFM Low-Profile Lighted Bathroom Exhaust Fan



- ENERGY STAR rated
- Virtually silent EC motor with 3 high speeds (50-80-110 CFM)
- Constant CFM technology
- 3-1/2 Inch Housing Depth the low profile is ideal for wall or ceiling installations. Easily fits in a 2x4 stud bay
- L-shaped bracket for support and ease of installation
- ETL listed for tub/shower enclosure when GFCI protected
- 10W dimmable LED chip panel, 750 lumens, 3000K warm white color temperature, and Rated Life of 50,000 hours
- 3-year warranty on ECM motor and parts, excluding light



Α	В	С	D	Е	F	G	Н
12.125 in	10.25 in	5 in	3.5 in	2.5 in	3.75 in	10.375 in	13 in

Certifications

ETL

Home Ventilating Institute (HVI) ENERGY STAR® Certified

Performance Characteristics

No Fan Curve Available.

Construction Features

Drive Type	Direct Drive			
Impeller Type	Centrifugal Wheel			
Impeller Material	Polypropylene			
Includes	Backdraft damper Mounting brackets			
Certifications	ETL Home Ventilating Institute (HVI) ENERGY STAR® Certified			
Speed Controllable	Yes			

Motor Information

Motor Phase	1	
Voltage	115	
Hertz	60	
Watte	22.6	

Air and Sound Performance

Watts	Max Fan RPM	Min Fan RPM	Ps (in. wg)	0.1	0.25	0.4	0.5
14.3	771	771	CFM	50	50	50	50
			Sones	>0.3	0.7	1.4	2.1
18.5	871	871	CFM	80	80	80	80
			Sones	0.7	1.2	1.8	2.3
22.6	1063	1063	CFM	110	110	110	110
			Sones	1.5	2.1	2.2	2.3

California Residents



⚠ WARNING

This product can expose you to chemicals including cadmium used in the processing of corrosion resistant metal and fasteners, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information visit www.P65Warnings.ca.gov